

## Portable Barcode label printers for mobile applications

## Compuprint 6010

With Compuprint 6010 on hand, label printing becomes so simple between your fingertips.

Compuprint 6010 powered is by high capacity lithium-ion battery, armored with water/dust/ shock resistant feature, supported with drop-and-fit design; it is your ultimate weapon to take on the challenges from mobile applications in retail / warehouse & storage / parking receipt industry and many more.

- Ultra light, compact and portable
- Rugged design passed 1.5m drop test
- Bluetooth 4.0/BLE Dual Mode
- USB charging at your convenience
- Long-lasting battery life (5 days stand-by)
- Support various of 1D &2D barcode printing
- Multiple wireless interfaces: support Android, WinCE, iOS
- OLED display
- MSR for option



Rugged Design



Easy Wireless Connection



OLED Screen









## **COMPUPRINT WE PRINT YOUR IDEAS**

## **Specification**

| Item           |                 | Parameter                                          |
|----------------|-----------------|----------------------------------------------------|
| Printing       | Printing Method | Direct Thermal Line Printing                       |
|                | Resolution      | 203dpi (8dots/mm)                                  |
|                | Printing Speed  | Max.110mm/s                                        |
|                | Printing Width  | 48mm                                               |
|                | Interface       | USB, Bluetooth 4.0                                 |
| Power Saving   | Sleep Mode      | YES                                                |
| Memory         | RAM             | 32Mb                                               |
|                | Flash           | 64Mb                                               |
| Resident Fonts | Font            | FONT A 12X24;FONTB 8X16;                           |
|                |                 | CHN 24X24;16X16;                                   |
|                | Alphanumeric    | 95                                                 |
|                | Codepage        | 48                                                 |
| Barcode        | 1D              | UPC-A, UPC-E, JAN/EAN8, JAN/EAN13, CODE39,         |
|                |                 | ITF, CODEBAR, CODE128, CODE93                      |
|                | 2D              | QR code, PDF417                                    |
| 0 11           |                 | Support bitmap printing with different density and |
| Graphics       |                 | user defined bitmap printing                       |
| Detection      | Sensors         | Paper out/Black mark/Gap label sensor, Cover       |
|                |                 | open switch                                        |
| LED indicator  | Power Indicator | Green                                              |
|                | Error Indicator | Red                                                |

| Power                       | Input           | AC 100 -240V                         |  |
|-----------------------------|-----------------|--------------------------------------|--|
|                             | Output          | DC 5V/1A                             |  |
|                             | Battery         | 1300mAh/7.4V rechargeable Li-ion     |  |
|                             |                 | battery                              |  |
| Paper                       | Paper Type      | Continuous paper, black mark paper,  |  |
|                             |                 | linerless label, gap label           |  |
|                             | Paper Width     | 58mm                                 |  |
|                             | Paper Thickness | 0.053~0.1mm                          |  |
|                             | Paper Roller    | ≤40mm                                |  |
|                             | Diameter        |                                      |  |
|                             | Paper Loading   | Easy paper loading                   |  |
| Environment                 | Operation       | -5°C~50°C , 25%~85%RH                |  |
| Environment                 | Storage         | -20°C~70°C, 5%~95%RH                 |  |
| Physical<br>Characteristics | Dimension       | 126.9(L)*84.4(W)*50.6(H)mm           |  |
|                             | Weight          | 234G (Without paper roll)            |  |
| Options & Accessories       |                 | USB Cable, Belt Clip, Charger ,Paper |  |
|                             |                 | Roll, Quick Start Guide, CD          |  |
| Software                    | Emulation       | ESC/POS                              |  |
|                             | Driver          | Windows XP/Vista/7/8/10/Linux/OPOS   |  |
|                             | SDK             | WinCE, Win Mobile, Android, iOS      |  |































Compuprint S.r.l.

Via Cottolengo 75-77-79 10072 Caselle T.se (TO) Sales Contact Tel. +39 011 9892 141 - Fax +39 011 9974432 sales@compuprint.com www.compuprint.com