



Impact solutions for industrial and business environments

Compuprint

9058
9058D

The Compuprint 9000 family is designed to meet the most demanding requirements of today's applications while offering unmatched performance in Windows and graphic printing environments. The ideal solution for mission critical requirements, with the full flexibility to support a variety of forms and documents.



Value and Features

- Long life 24 pins print-head technology
- 480 cps at 10cpi up to 720 cps max speed
- Superior performance in volume printing
- Dual front straight paper paths
- 8 copies capability
- Simple to use, pre-set configurations
- Wide range of barcodes and macro-characters

A leading-edge series for today and tomorrow

Compuprint 9058 and 9058D integrate the latest technology and innovation based on more than 30 years of Compuprint leadership in the serial printer technology.

It represent the preferred choice for business and industrial printing applications requiring up to 40,000 pages per month workload, providing the best investment for many years of worry free service.

Fast, flexible, reliable

Compuprint 9058 and 9058D are built on state-of-the art technologies and innovative functionalities. With the two configurations, including the single sheet and one tractor (9058) or the dual front tractors (9058D), these models cover all the most common paper handling requirements. These models provide superior performance in traditional impact applications and high levels of flexibility and automation for the user with a unique paper path for superb reliability.

For a broad range of connectivity and printing requirements

A large number of character sets, fonts and barcodes combined with a wide set of interfaces and protocols allow the printer to connect in most contemporary environments and to be the ideal solution for industrial requirements for printing macro characters, barcodes and pre-printed forms.



Printing Technology	24 pin serial dot matrix printer
Printing speed	Max: 720 cps · 15 cpi · 12 cpi · 10 cpi Draft 720 cps 576 cps 480 cps LQ 200 cps 160 cps 133 cps
Throughput (ISO/IEC 10561)	430 pph
Line Length	136 columns @ 10 cpi
Paper handling	Continuous form: front loading Front single sheet + front push tractor (9058) Dual front push tractor (9058D) Rear pull tractor (optional) (width from 76 to 432 mm - maximum thickness 0.64 mm) Automatic sheet feeder for single sheets (optional): up to three bins (120 sheets @ 80 gr/m2 capacity each - width from 89 to 305 mm - 1+2 copies)
Copies	1 + 7
Special functions	Automatic paper path alternance Automatic Gap Adjustment (AGA) of print head based on paper thickness Zero tear-off Automatic paper parking of continuous form
Graphic resolution (dpi)	60, 80, 90, 120, 180, 240, 360 (horizontal) 60, 72, 180 (vertical)
Vertical spacing	6 - 8 - 12 lines per inch; 3 - 4 - 6 - 8 - 12 lines per 30 mm.; n/60, n/72, n/180, n/216, n/360 per inch
Horizontal spacing	10, 12, 15, 17.1, 20, 24 cpi and proportional
Barcodes	UPC/A, UPC/E, EAN8, EAN13 - UPC/EAN ADD-ON 5, UPC/EAN ADD-ON 2 - Code 39 - Code 128 - Code 11- Code 93 - MSI - Postnet - Codabar - 2/5 Interleaved -2/5 Matrix - 2/5 Industrial - Code GP - C25-3BAR - Code BCD - 2/5 Bidirectional
Character set	Standard PC IBM character sets: CS1, CS2 ; 13 EPSON national variations IBM and EPSON character sets: CP 437 (USA), CP437G (Greek), CP437SL (Slavic), CP850 (Multilingual), CP851 (Greek), CP852 (Eastern Europe), CP853 (Turkish), CP855 (Cyrillic), CP857 (Turkish), CP858 (Euro PC Multilingual), CP860 (Portugal), CP862 (Hebrew), CP863 (French-Canadian), CP864 (Arabic), CP865 (Danish-Norwegian), CP866 (Russian), CP867 (Turkish2), CP876 (OCR-A), CP877 (OCR-B), CP1098 (Farsi), CP1250 (Latin2 Windows), CP1251 (Cyrillic Windows), CP1252 (Latin1 Windows), CP1253 (Greek Windows), CP1254 (Turkish Windows), CP1255 (Hebrew Windows), CP1256 (Arabic Windows), CP1257 (Baltic Windows), 96Greek, GOST, TASS, MAZOWIA, KOI8-U ISO character sets: 8859/1 (Latin1), 8859/2 (Latin2), 8859/3 (Latin3), 8859/4 (Latin4), 8859/5 (Latin/Cyrillic), 8859/6 (Latin/Arabic), 8859/7 (Latin/Greek), 8859/8 (Latin/Hebrew), 8859/9 (Latin5), 8859/15 (Latin9)
Resident font	Draft, Courier, Gothic, OCR-A, OCR-B, Script, Prestige, Presentor
Resident Emulations	Epson ® LQ 1050-2550 (ESC/P), IBM ® Proprinter XL24E-L24AGM, IBM ® Personal Printer 2391+
Interfaces	Centronics, Parallel IEEE1284 bidirectional, Serial RS232-C, RS422-A Input buffer up to 128 Kbytes Plug&play (Windows environment)
Reliability	MTBF: 10.000 hours
Print Head Life	400 million characters
Ribbon life	Black ribbon 15 MC, Long life ribbon 20 MC (optional)
Noise Level	54 dBA
Power Supply	Tension: 120V - 220/240V Frequency: 60 Hz - 50 Hz
Power consumption	116 W Max. (printing), 22 W (standby)
Physical Dimensions & Weight	670 (W) x 315 (H) x 320 (D) mm - 21 Kg


SFERAL WWT - Compuprint SALES CONTACTS

Italy: (+39) 011 9892 141 -
 Other Countries: (+39) 011 9892 141 -
 Email: sales@sferalwwt.com -
 Website: www.sferalwwt.com -


Ordering Information
Printers and Supplies

Compuprint 9058 (single sheet, single tractor)	PRTN958
Compuprint 9058D (dual tractor)	PRTN959
Black ribbon cartridge 15 MC	PRKN407-1
Black ribbon cartridge 20 MC	PRKN707-1
Colour ribbon cartridge 2 MC each colour	PRKN408-1

Options

3 levels pedestal	PRFN405-0000
Floor pedestal with adjustable height setting	PRFN406-0000
Pull tractor	PRF9000
Kit for colour ribbon & long life black ribbon	KITN401-0000

The information contained in this document is subject to change without notice. All company and product names mentioned herein are trademarks or registered trademarks of their respective owners.
 Copyright © 2007 Sferal wwt

ENBROCH-MAY05