

Compuprint 3056/N

The Compuprint 3056 and 3056N are designed to be the ideal solution for administrative applications as well for industrial and logistics environments.

These printers satisfy a wide range of printing solutions thanks to the architectural simplicity of the front form feed and refined printing technology.

Compuprint 3056 and 3056N are suited for printing applications using multipart forms, single sheets, labels and envelopes.



Value and Features

- 24 pins print-head technology
- 560 cps speed
- Complete and flexible paper path
- Single sheet and fanfold handling
- 1+5 copies capability
- Wide range of connectivity
- Easy to use
- Wide range of barcodes and fonts

Matching your needs and getting your job done in time

Compuprint 3056 and 3056N are ideal for use in a broad range of industries, from data processing, banking, pharmaceuticals or healthcare, warehouse and logistic, education and public administrations.

These printers in single or multi-user environments print at speeds of up to 560 characters per second in draft mode offering an excellent print quality with clear, crisp output of text and graphics.

Safe and simple paper management

Thanks to the possibility to choose either front or rear paper feed these printers are the best solution for all types of working environment. Straight feeding enables a wide variety of both single sheet, continuous and multiple copy forms to be managed in a safe and reliable manner.

It is also possible to install both printers a second tractor to improve the productivity.

For a broad range of connectivity

Compuprint 3056 is available in two different configurations, Parallel/Serial/USB or Parallel/USB/LAN to let the user able the installation on networked environment. The LAN models are provided with a Network Interface Manager which is a software used to manage on-line network dot matrix printers.



Printing Technology	24 pin - serial dot matrix printers															
Printing resolution	360 x 180 dpi															
Printing speed	<table border="1"> <thead> <tr> <th>Mode</th> <th>12 cpi</th> <th>10 cpi</th> </tr> </thead> <tbody> <tr> <td>HDS</td> <td>650 cps</td> <td>560 cps</td> </tr> <tr> <td>Draft</td> <td>520 cps</td> <td>480 cps</td> </tr> <tr> <td>NLQ</td> <td>288 cps</td> <td>240 cps</td> </tr> <tr> <td>LQ</td> <td>144 cps</td> <td>120 cps</td> </tr> </tbody> </table>	Mode	12 cpi	10 cpi	HDS	650 cps	560 cps	Draft	520 cps	480 cps	NLQ	288 cps	240 cps	LQ	144 cps	120 cps
Mode	12 cpi	10 cpi														
HDS	650 cps	560 cps														
Draft	520 cps	480 cps														
NLQ	288 cps	240 cps														
LQ	144 cps	120 cps														
Line Length	136 columns @ 10 cpi															
Paper handling	Cut sheet: width from 101 to 420 mm / A5, A4, A3 (H/V) - length up to 364 mm Continuous form: width from 101 to 406 mm - length unlimited Paper thickness: 0,065 to 0.52 mm															
Paper type	Cut sheet, Continuous paper, Multi-part forms, Envelopes, postcard, adhesive labels															
Paper path	Friction feed: rear in top out, front in top out - Tractor feed: rear in top out, front in top out, bottom in top out															
Copies	1 + 5															
Special functions	Automatic paper parking, Zero tear-off															
Barcodes	UPC/A - EAN8 - EAN13 - UPCA/E - Code 39 - Code 128 - 2/5 Interleaved - Postnet															
Character set	ASCII, Italic, CP437, CP850, CP860, CP863, CP865, CP858, CP737 (437G), CP857, CP1250, CP864, CP1098, CP1256 International Character Set: USA, France, Germany, England, Denmark, Sweden, Italy, Spain, Japan, Norway, Denmark 2, Spain 2, Latin America, Korea, Legal															
Resident font	Draft, Courier, Roman, Sans Serif, Prestige, Script, Orator, Orator-S, OCR-A, OCR-B															
Resident Emulations	Epson ® LQ-ESC/P, OKI, IBM ProPrinter (PPDS)															
Interfaces	Centronics, Parallel IEEE 1284 bidirectional - Serial RS232 - USB (Base models) Centronics, Parallel IEEE 1284 bidirectional - USB - Ethernet LAN 10/100 BaseT (N models) Input buffer up to 128 Kbytes; Automatic interface switching; Plug-in & Play (Windows environment)															
Drivers	Windows 95/98/2000/XP/Vista/Win7/Win8/Win10 - Unix - Linux															
SW Tool	Network Interface Manager - Internal web page															
Reliability	MTBF: 20.000 hours at 25% Duty Cycle MPVBF: 24 million lines (except print head)															
Print Head Life	400 million strokes/wire															
Ribbon life	up to 10 million characters															
Noise Level	<55 dBA															
Power Supply	Tension: 100-240V; Frequency: 50-60Hz															
Power consumption	75 W Max. (printing), 15 W (standby)															
Physical Dimensions & Weight	623 (W) x 395 (D) x 173 (H) mm - 13 Kg															



Compuprint SALES CONTACTS

Italy: (+39) 011 9892 141 -
Other Countries: (+39) 011 9892 141 -
Website: www.compuprint.com
Email: sales@compuprint.com



Ordering Information

Printers and Supplies

Compuprint 3056 Basic Printer (P-S-U)	PRTN3056
Compuprint 3056 LAN Printer (P-U-N)	PRTN3056N

Compuprint Black Ribbon Cartridges(8 pcs)	PRK3050-8
---	-----------

Options

Optional second tractor	PRFN3056
-------------------------	----------

The information contained in this document is subject to change without notice. All company and product names mentioned herein are trademarks or registered trademarks of their respective owners.
Copyright © March 2017 Compuprint.